



VGA Cat5/5e/6 Splitter/Extender

Distributes video and audio signals up to 300 m (984 ft.)

Model
177252

Easily distribute a single VGA audio and video signal to multiple locations.

The MANHATTAN® VGA Cat5/5e/6 Splitter/Extender helps lengthen VGA and audio signals from a single source to remote locations using Cat5/5e/6 cables.

Flexible Solution for Many A/V Applications

Ideal for trade shows, classrooms, home theater, conference rooms, business office and retail applications, the MANHATTAN VGA Cat5/5e/6 Splitter/Extender allows the remote placement of up to four displays and speaker sets from a single desktop or notebook computer source 300 m (984 ft.) away. Manual brightness and RGB adjustments help fine-tune images for optimum signal clarity. Easy to install and readily available, Cat5e or Cat6 twisted-pair cables when combined with the MANHATTAN VGA Cat5/5e/6 Splitter/Extender help provide additional protection from external interference over longer distances and customized lengths without signal degradation.


Quality Construction and Easy Installation

Quickly connect Cat5e or Cat6 cables (not included) and the power supplies without software or hardware configuration or complicated settings to complete an affordable VGA distributed signal solution.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.





Above: Splitter/Extender;
Right: Receiver



Model
177252

Features

- Easily extends VGA and audio signals using Cat5/5e/6 cables for longer distance transmissions
- Helps provide more convenient placements from a single source to up to four displays
- Supports VGA resolutions up to 1600 x 1440
- Delivers a sharp, clear signal with RGB and brightness adjustments
- Easy installation — no software required
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS

- CE
- FCC

GENERAL

- Extends transmission range up to 300 m
- Supports up to 1600 x 1440 resolution and VGA, SVGA, Multisync signal types
- Manual RGB and brightness adjustments
- (2) 9 V DC / 1 A power adapters included

CONNECTIONS

- Splitter/extender: (1) HD15 female (out), (1) HD15 male (in), (2) 3.5 stereo ports (in/out), (4) RJ45, (1) 9 V DC power ports
- Receiver: (1) HD15 female, (1) RJ-45 female, (1) 3.5mm stereo, (1) 9 V DC power ports

VIDEO SIGNAL

- Signal type: VGA
- Input voltage: 0.5 V p-p / 2.0 V p-p (minimum/maximum)
- I/O impedance: 75 Ohms

PHYSICAL (RECEIVER)

- Dimensions: 120 x 72 x 25 mm (4.7 x 2.8 x 1 in.)
- Weight: 252.3 kg (8.9 oz.)
- Housing: metal

PHYSICAL (SPLITTER/EXTENDER)

- Dimensions: 203 x 112 x 42 mm (8 x 4.4 x 1.6 in.)
- Weight: 720 g (25.4 oz.)
- Housing: metal

PACKAGE CONTENTS

- VGA Cat5/5e/6 Splitter/Extender with Receiver
- Power adapters
- Reference guide

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.


MANHATTAN[™]
BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

MH-177252-DS-0908-01