



HDMI Splitter

HDMI 1.3b, 2-Port

Model
177337

Easily distribute a single HDMI signal to multiple displays.

The MANHATTAN® HDMI Splitter helps send HDMI (High-Definition Multimedia Interface) signals from a single HD DVD or Blu-ray player, satellite receiver, digital recorder, set-top box, game console or other HDMI source to additional HDMI displays.

Flexible Solution for Many A/V Applications

Ideal for trade shows, classrooms, video conferencing and presentations and retail applications, the MANHATTAN HDMI Splitter features a built-in booster for added signal strength. It's also a good choice for splitting and distributing a synchronous signal to multiple HDMI displays when source equipment is remotely stored in a secured room or cabinet. Cascade multiple units up to three levels to output HDMI video/audio to additional displays in widely distributed applications.

Quality Construction and Easy Installation

Full compliance with HDMI 1.3b, HDCP 1.0, 1.1 and 1.2 and DVI 1.0 ensures that the MANHATTAN HDMI Splitter can provide long service and reliable performance. Quickly connect HDMI cables (not included) and the power supply without software or hardware configuration or complicated settings to complete an affordable HDMI solution.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.





Model
177337

Features

- Duplicates a high-definition digital audio/video signal for two HDMI outputs
- Supports video amplifier bandwidths up to 2.25 Gbps / 225 MHz
- Delivers a sharp, clear signal from DVD and Blu-ray players, set-top box, satellite receiver and other sources
- Fully HDCP compliant to protect high-definition content transmission and ensure quality reception
- Cascade up to three levels to expand signal distribution to more displays
- Easy to install — requires no configuration
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS

- HDMI 1.3b
- HDCP 1.0 / 1.1 / 1.2
- DVI 1.0
- CE
- FCC
- UL

GENERAL

- Source-to-splitter range: up to 15 m (49 ft.)
- Splitter-to-display range: up to 15 m (49 ft.)
- Power: 5 V DC / 2 A; cable with ferrite core, 1.2 m (4 ft.)

CONNECTIONS

- (1) HDMI female (input)
- (2) HDMI female (output)

SIGNAL INPUT/OUTPUT

- Input video signal: 0.5 – 1.0 V p-p
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 2.25 Gbps, 1920 x 1200, 1080p
- Output video: HDMI 1.3b, HDCP 1.0 / 1.1 / 1.2, DVI 1.0
- Frequency: 2.25 Gbps / 225 MHz

VIDEO RESOLUTIONS

- VGA: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200
- DTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p

PHYSICAL

- LED indicators: power and port connection
- Dimensions: 155 x 70 x 23 mm (6.1 x 2.75 x 0.9 in.)
- Weight: 260 g (9.2 oz.)

PACKAGE CONTENTS

- HDMI Splitter
- Power adapter
- User manual

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.


BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

MH-177337-DS-0908-01